

Technical Specification

reelba

45 Tonne Max Outreach 3900 mm from (centre-line)

Side of Lift Right Hand Lift

Tilt & Extend (Foot size: 730x220) Stabilisers

Lifting Chains 16 mm Grade 120 RUD ICE

Chain Shorteners Optional

Max Lift Capacity

Container Detection Proximity sensor and lights Work Lamps Fitted to each stabiliser leg

> **Hydraulics** Danfoss PVG32 proportional valve

Crane Paint Traffic Red (RAL 3020)

Interface

Centre drive; optimum 20', rear 20', 2x20', 40' **Container Position**

SmartLift Control System

Remote Control Radio remote joystick control

Control Cabinet Steel, lockable

> Toolbox Steel, lockable 500 mm (Grey)

To lift 2x20' ISO containers simultaneously **Container Joiners**

Power Supply

PTO (optional supply - supplied on request) Source Advise truck specifications (Must specify)

Voltage 24V

Spec

Refer truck unit specifications **Emissions** Pump Refer truck/PTO specifications Mounting Refer truck/PTO specifications Refer truck/PTO specifications Tank

Chassis

Chassis Model Trombone Chassis (20-40')

Rubplate Height (RPH) 1350mm

4161mm (ISO 8'6" container) Overall Height (OAH)

> Standard 2" (bolted) Kingpin

Landing Legs Dual speed, wind up legs

Landing Leg Handle Right hand side Suspension SAF Air Suspension

> SAF 22.5 10/335 disc brake Axles

Axle 1 Rigid/Lift Axle 2 Steer (forced) Axle 3 Steer (forced)

Steel 11.75x22.5 Wheels 385/65R 22.5"

Wabco EBS **Brake System**

Gladhand couplings (Red/Yellow) **Brake Coupling**

Trailer Wiring ADR

Tyres

Lighting Multi-Volt LED

Electrical Coupling 15-pin plug (ISO 12098) & EBS plug

> Plastic, Black with alloy joiner Mudguards

Mud Flaps 2x single flaps

Spare Wheel Carrier Optional (crane mounted)

> **Paint** Traffic Red (RAL 3020)

Sales Drawing SB450TS2040-G013E

Tare Weight 13000 kg ± 3% (Subject to final specification)







